



KÖCO UT

DIN EN ISO 13918

Unthreaded stud with flange and ignition tip

- Part.no. applies to steel, grade 4.8, copper plated
- Other types and dimensions upon request. Not a part from warehouse, minimum quantities are needed.



d_1	l_1	d_2	d_4	l_3	h_1	Part-no.	Mass kg/100	Chuck
3	8	4,5	0,6	0,55	0,7 - 1,4	101-0021-103	0,049	351-7003-000
	10					101-0022-103	0,060	
	12					101-0023-103	0,071	
	16					101-0025-103	0,093	
	20					101-0026-103	0,116	
4	8	5,5	0,65	0,55	0,7 - 1,4	101-0051-103	0,086	351-7004-000
	10					102-0052-103	0,106	
	12					101-0053-103	0,125	
	16					102-0054-103	0,165	
	20					102-0056-103	0,204	
5	12	6,5	0,75	0,8	0,7 - 1,4	102-0086-103	0,197	351-7005-000
	16					102-0089-103	0,257	
	20					102-0090-103	0,319	
	25					102-0091-103	0,396	
6	12	7,5	0,75	0,8	0,7 - 1,4	102-0118-103	0,279	351-7006-000
	16					101-0120-103	0,367	
	20					101-0121-103	0,456	
	25					101-0122-103	0,567	
7,1	16	9	0,75	0,85	0,8 - 1,4	101-0163-103	0,496	351-7008-000
	20					101-0164-103	0,620	
	25					101-0165-103	0,775	

$l_2 \approx l_1 - 0,3 \text{ mm}$.

